

View Online at <https://aerobasegroup.com/nsn/5990-00-568-4932>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round d

Shoulder Diameter:

Between 1.9850 inches and 1.9950 inches

Pilot Diameter:

Between 0.5950 inches and 0.6000 inches

Second Shoulder Diameter:

Between 1.9985 inches and 1.9995 inches

Second Shoulder Length:

Between 0.1640 inches and 0.1700 inches

Overall Length:

Between 4.2430 inches and 4.2990 inches

Flange Diameter:

Between 2.2400 inches and 2.2500 inches

Flange Thickness:

Between 0.2480 inches and 0.2500 inches

Body Diameter:

Between 1.9850 inches and 1.9950 inches

Shaft Diameter:

0.2402 inches single shaft and 0.2405 inches single shaft

Shaft Length:

0.6920 inches single shaft and 0.7180 inches single shaft

Body Size:

23

Stator Input Voltage Rating In Volts:

90.0

Stator Input Current Rating:

19.0 milliamperes

Stator Input Electrical Power Rating:

85.0 milliwatts

Frequency In Hertz:

400.0

Zro Impedance Magnitude In Ohms:

3200.00

Zro Impedance Angle In Deg:

86.00

Phase Shift Angle In Deg:

1.900 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

20.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Pilot Length:

Between 0.0330 inches and 0.0430 inches

Shoulder Length:

0.2500 inches

Aft Of First Flange Diameter:

Between 1.9985 inches and 1.9995 inches

Mounting Surface To Terminal End Distance:

Between 3.5250 inches and 3.5810 inches

Shaft Thread Series Designator:

Unf single shaft

Shaft Thread Direction:

Right-hand single shaft

Shaft Thread Class:

2a single shaft

Terminal Location:

Rear

Shaft Thread Length:

0.3100 inches single shaft

Shaft Type:

Round single shaft

Transformation Ratio:

0.980 rotor to stator

Shaft Thread Size:

0.250 inches single shaft

Terminal Type And Quantity:

14 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800