

View Online at <https://aerobasegroup.com/nsn/5990-00-578-7015>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.8118 inches and 0.8123 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6560 inches

Flange Diameter:

Between 0.9360 inches and 0.9370 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.8400 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.3750 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

10

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

90.0 milliamperes

Rotor Input Electrical Power Rating:

440.0 milliwatts

Zro Resistance In Ohms:

54.00

Rotor Dc Resistance In Ohms:

33.00

Stator Dc Resistance In Ohms:

11.50

Phase Shift Angle In Deg:

6.500 input to output

Receiver Error Angular Range In Minutes:

-15.0/+15.0

Pilot Length:

0.0380 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.2810 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

285.00

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0300 inches single shaft

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800