

View Online at <https://aerobasegroup.com/nsn/5990-00-583-3701>

**Body Material:**

Aluminum

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.9995 inches and 1.0000 inches

**Pilot Diameter:**

Between 0.6245 inches and 0.6250 inches

**Overall Length:**

2.1700 inches

**Flange Diameter:**

Between 1.0570 inches and 1.0650 inches

**Flange Thickness:**

0.0930 inches

**Undercut Diameter:**

0.9750 inches

**Undercut Width:**

0.0500 inches

**Shaft Diameter:**

0.1195 inches single shaft and 0.1200 inches single shaft

**Shaft Length:**

0.3740 inches single shaft

**Fragility Factor:**

Moderately rugged

**Maximum Temperature Rise:**

15.0 degrees celsius

**Body Size:**

11

**Rotor Input Voltage Rating In Volts:**

26.0

**Frequency In Hertz:**

400.0

**Rotor Input Current Rating:**

90.0 milliamperes

**Rotor Input Electrical Power Rating:**

300.0 milliwatts

**Zro Impedance Magnitude In Ohms:**

359.00

**Zro Impedance Angle In Deg:**

81.30

**Zso Impedance Magnitude In Ohms:**

60.00

**Zso Impedance Angle In Deg:**

78.50

**Rotor Dc Resistance In Ohms:**

28.50

**Stator Dc Resistance In Ohms:**

10.50

**Phase Shift Angle In Deg:**

4.700 input to output

**Maximum Fundamental Null Voltage In Millivolts Per Volt:**

17.00 output

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

26.00

**Pilot Length:**

0.0620 inches

**Shoulder Length:**

0.0620 inches

**Mounting Surface To Terminal End Distance:**

1.7960 inches

**Terminal Location:**

Rear

**Shaft Slot Depth:**

0.0300 inches single shaft

**Shaft Slot Width:**

0.0250 inches single shaft

**Shaft Type:**

Round, slotted single shaft

**Transformation Ratio:**

0.454 rotor to stator

**Terminal Type And Quantity:**

5 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A07800