Control Transformer Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-583-3724

| Body Material: | |
|---|--|
| Aluminum | |
| Body Style: | |
| Standard round c | |
| Shoulder Diameter: | |
| Between 1.3115 inches and 1.3120 inches | |
| Pilot Diameter: | |
| Between 0.4995 inches and 0.5000 inches | |
| Overall Length: | |
| 2.1310 inches | |
| Flange Diameter: | |
| Between 1.4360 inches and 1.4370 inches | |
| Flange Thickness: | |
| 0.0930 inches | |
| Undercut Diameter: | |
| 1.3120 inches | |
| Undercut Width: | |
| 0.0780 inches | |
| Shaft Diameter: | |
| 0.1200 inches single shaft | |
| Shaft Length: | |
| 0.5400 inches single shaft | |
| Body Size: | |
| 15 | |
| Stator Input Voltage Rating In Volts: | |
| 11.8 | |
| Stator Input Current Rating: | |
| 25.0 milliamperes | |
| Stator Input Electrical Power Rating: | |
| 70.0 milliwatts | |
| Frequency In Hertz: | |
| 400.0 | |
| Zro Resistance In Ohms: | |
| 125.00 | |
| Rotor Dc Resistance In Ohms: | |
| 250.00 | |
| Stator Dc Resistance In Ohms: | |
| 63.00 | |
| Electrical Error Angular Range In Minutes: | |
| -10.0/+10.0 | |
| Actuator Friction Torque At Minus 55 Deg Celsius: | |
| 15.0 centimeter-grams | |
| | |



Actuator Friction Torque At Plus 25 Deg Celsius: 3.0 centimeter-grams **Alignment Hole Quantity:** 4 **Pilot Length:** 0.0400 inches Shoulder Length: 0.1320 inches Mounting Surface To Terminal End Distance: 1.5310 inches **Terminal Location:** Rear Plus J Zro Reactance In Ohms: 480.00 Shaft Slot Depth: 0.0210 inches single shaft and 0.0310 inches single shaft Shaft Slot Width: 0.0210 inches single shaft and 0.0310 inches single shaft Shaft Type: Round, slotted single shaft Alignment Hole Depth: 0.1250 inches Alignment Hole Bolt Circle Diameter: 0.8750 inches **Terminal Type And Quantity:** 5 wire lead Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A07800

--