

View Online at <https://aerobasegroup.com/nsn/5990-00-583-9217>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 1.5615 inches and 1.5620 inches

Pilot Diameter:

Between 0.9370 inches and 0.9375 inches

Overall Length:

3.2500 inches

Flange Diameter:

Between 1.7470 inches and 1.7500 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

1.6250 inches

Undercut Width:

0.0780 inches

Shaft Diameter:

0.1870 inches single shaft and 0.1872 inches single shaft

Shaft Length:

0.5400 inches single shaft

Maximum Temperature Rise:

60.0 degrees celsius

Body Size:

18

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

60.0

Rotor Input Current Rating:

105.0 milliamperes

Rotor Input Electrical Power Rating:

4.0 watts

Electrical Error Angular Range In Minutes:

-8.0/+8.0

Spline Tooth Quantity:

21 single shaft

Torque Gradient Per Angular Deg:

0.050 inch-ounces

Alignment Hole Quantity:

4

Pilot Length:

0.0400 inches

Shoulder Length:

0.1320 inches

Mounting Surface To Terminal End Distance:

2.5200 inches

Spline Tooth Diametral Pitch:

120 single shaft

Shaft Thread Series Designator:

Unf single shaft

Shaft Thread Direction:

Right-hand single shaft

Shaft Thread Class:

2a single shaft

Terminal Location:

Rear

Shaft Thread Length:

0.2000 inches single shaft

Shaft Type:

Spline w/threads single shaft

Alignment Hole Depth:

0.1250 inches

Transformation Ratio:

0.783 rotor to stator

Alignment Hole Bolt Circle Diameter:

1.2500 inches

Shaft Thread Size:

0.190 inches single shaft

Terminal Type And Quantity:

5 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800