NSN 5990-00-583-9217

Transmitter Synchro - Page 1 of 2

Body Material:

Steel, corrosion resisting



View Online at https://aerobasegroup.com/nsn/5990-00-583-9217

Body Style:
Standard round c
Shoulder Diameter:
Between 1.5615 inches and 1.5620 inches
Pilot Diameter:
Between 0.9370 inches and 0.9375 inches
Overall Length:
3.2500 inches
Flange Diameter:
Between 1.7470 inches and 1.7500 inches
Flange Thickness:
0.0930 inches
Undercut Diameter:
1.6250 inches
Undercut Width:
0.0780 inches
Shaft Diameter:
0.1870 inches single shaft and 0.1872 inches single shaft
Shaft Length:
0.5400 inches single shaft
Maximum Tempurature Rise:
60.0 degrees celsius
Body Size:
18
Rotor Input Voltage Rating In Volts:
115.0
Frequency In Hertz:
60.0
Rotor Input Current Rating:
105.0 milliamperes
Rotor Input Electrical Power Rating:
4.0 watts
Electrical Error Angular Range In Minutes:
-8.0/+8.0
Spline Tooth Quantity:
21 single shaft
Torque Gradient Per Angular Deg:
0.050 inch-ounces

Alignment Hole Quantity:

NSN 5990-00-583-9217 Transmitter Synchro - Page 2 of 2



Pilot Length:
0.0400 inches
Shoulder Length:
0.1320 inches
Mounting Surface To Terminal End Distance:
2.5200 inches
Spline Tooth Diametral Pitch:
120 single shaft
Shaft Thread Series Designator:
Unf single shaft
Shaft Thread Direction:
Right-hand single shaft
Shaft Thread Class:
2a single shaft
Terminal Location:
Rear
Shaft Thread Length:
0.2000 inches single shaft
Shaft Type:
Spline w/threads single shaft
Alignment Hole Depth:
0.1250 inches
Transformation Ratio:
0.783 rotor to stator
Alignment Hole Bolt Circle Diameter:
1.2500 inches
Shaft Thread Size:
0.190 inches single shaft
Terminal Type And Quantity:
5 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A07800