

View Online at <https://aerobasegroup.com/nsn/5990-00-583-9577>

Body Material:

Aluminum

Body Style:

Standard round c

Shoulder Diameter:

0.9750 inches

Pilot Diameter:

0.6250 inches

Overall Length:

2.0840 inches

Flange Diameter:

1.0620 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

1.0000 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1200 inches single shaft

Shaft Length:

0.3500 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

39.0 milliamperes

Rotor Input Electrical Power Rating:

1.0 watts

Zro Impedance Magnitude In Ohms:

107.00

Zro Impedance Angle In Deg:

81.70

Zso Impedance Magnitude In Ohms:

18.10

Zso Impedance Angle In Deg:

79.50

Rotor Dc Resistance In Ohms:

9.00

Stator Dc Resistance In Ohms:

3.00

Phase Shift Angle In Deg:

5.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

17.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

26.00

Actuator Friction Torque At Plus 25 Deg Celsius:

4.00 centimeter-grams

Torque Gradient Per Angular Deg:

5500.000 millimeter-milligrams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7340 inches

Terminal Location:

Rear

Shaft Type:

Round single shaft

Transformation Ratio:

0.454 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800