

View Online at <https://aerobasegroup.com/nsn/5990-00-583-9594>

Body Material:

Steel, stainless

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

Between 1.7620 inches and 1.7660 inches

Flange Diameter:

Between 0.4995 inches and 0.5000 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.6870 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.4610 inches single shaft and 0.4750 inches single shaft

Fragility Factor:

Moderately rugged

Maximum Temperature Rise:

3.0 degrees celsius

Body Size:

8

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

145.0 milliamperes

Stator Input Electrical Power Rating:

380.0 milliwatts

Frequency In Hertz:

400.0

Zro Impedance Magnitude In Ohms:

79.00

Zro Impedance Angle In Deg:

73.00

Zso Impedance Magnitude In Ohms:

110.00

Zso Impedance Angle In Deg:

68.50

Rotor Dc Resistance In Ohms:

40.00

Stator Dc Resistance In Ohms:

25.00

Phase Shift Angle In Deg:

14.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

17.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

26.00

Electrical Error Angular Range In Minutes:

-10.0/+10.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.00 centimeter-grams

Pilot Length:

0.0400 inches

Mounting Surface To Terminal End Distance:

1.2810 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

1.154 rotor to stator

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A07800