

View Online at <https://aerobasegroup.com/nsn/5990-00-600-6151>

Body Material:

Any acceptable

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

2.2320 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

Between 0.0900 inches and 0.0960 inches

Undercut Diameter:

Between 0.9700 inches and 0.9800 inches

Undercut Width:

Between 0.0450 inches and 0.0550 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.4260 inches single shaft and 0.4500 inches single shaft

Body Size:

11

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

50.0 milliamperes

Rotor Input Electrical Power Rating:

970.0 milliwatts

Zro Impedance Magnitude In Ohms:

2598.00

Zro Impedance Angle In Deg:

81.80

Zso Impedance Magnitude In Ohms:

60.00

Zso Impedance Angle In Deg:

78.50

Rotor Dc Resistance In Ohms:

Between 207.10 and 228.90

Stator Dc Resistance In Ohms:

Between 8.925 and 12.075

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

3.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

0.3 centimeter-grams

Torque Gradient Per Angular Deg:

4000.000 millimeter-milligrams

Pilot Length:

Between 0.0590 inches and 0.0650 inches

Shoulder Length:

Between 0.0590 inches and 0.0650 inches

Mounting Surface To Terminal End Distance:

1.7960 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.152 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800