

View Online at <https://aerobasegroup.com/nsn/5990-00-607-0116>

**Body Material:**

Steel, stainless

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.9995 inches and 1.0000 inches

**Pilot Diameter:**

Between 0.6245 inches and 0.6250 inches

**Overall Length:**

Between 2.0980 inches and 2.1220 inches

**Flange Diameter:**

Between 1.0570 inches and 1.0650 inches

**Flange Thickness:**

0.0930 inches

**Undercut Diameter:**

0.9750 inches

**Undercut Width:**

0.0500 inches

**Shaft Diameter:**

0.1195 inches single shaft and 0.1200 inches single shaft

**Shaft Length:**

0.3450 inches single shaft

**Maximum Temperature Rise:**

5.0 degrees celsius

**Body Size:**

11

**Stator Input Voltage Rating In Volts:**

90.0

**Stator Input Current Rating:**

600.0 milliamperes

**Stator Input Electrical Power Rating:**

600.0 milliwatts

**Frequency In Hertz:**

400.0

**Zro Impedance Magnitude In Ohms:**

1990.00

**Zro Impedance Angle In Deg:**

77.30

**Zso Impedance Magnitude In Ohms:**

1640.00

**Zso Impedance Angle In Deg:**

80.70

**Rotor Dc Resistance In Ohms:**

385.00

**Stator Dc Resistance In Ohms:**

195.00

**Phase Shift Angle In Deg:**

4.700 input to output

**Maximum Fundamental Null Voltage In Millivolts Per Volt:**

59.00 output

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

94.00

**Electrical Error Angular Range In Minutes:**

-10.0/+10.0

**Actuator Friction Torque At Minus 55 Deg Celsius:**

16.00 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

4.00 centimeter-grams

**Pilot Length:**

0.0620 inches

**Shoulder Length:**

0.0620 inches

**Mounting Surface To Terminal End Distance:**

1.7050 inches

**Terminal Location:**

Rear

**Shaft Type:**

Round single shaft

**Transformation Ratio:**

1.154 rotor to stator

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A07800