

View Online at <https://aerobasegroup.com/nsn/5990-00-617-0535>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.8118 inches and 0.8123 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.4910 inches

Flange Diameter:

Between 0.9360 inches and 0.9370 inches

Flange Thickness:

0.0630 inches

Undercut Diameter:

0.8400 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.2500 inches single shaft

Body Size:

10

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

90.0 milliamperes

Rotor Input Electrical Power Rating:

440.0 allqjaa3.500 finished-chamfered

Zro Resistance In Ohms:

54.00

Zso Resistance In Ohms:

13.00

Zrs Resistance In Ohms:

80.00

Rotor Dc Resistance In Ohms:

33.00

Stator Dc Resistance In Ohms:

11.60

Phase Shift Angle In Deg:

6.500 input to output

Receiver Error Angular Range In Minutes:

-30.0/+30.0

Actuator Friction Torque At Minus 55 Deg Celsius:

5400.0 millimeter-milligrams

Actuator Friction Torque At Plus 25 Deg Celsius:

2700.0 millimeter-milligrams

Torque Gradient Per Angular Deg:

1800.0 millimeter-milligrams

Alignment Hole Quantity:

4

Pilot Length:

0.0380 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.2410 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

285.00

Shaft Slot Depth:

0.0300 inches single shaft

Plus J Zso Reactance In Ohms:

50.00

Shaft Slot Width:

0.0200 inches single shaft

Plus J Zrs Reactance In Ohms:

26.00

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800