

View Online at <https://aerobasegroup.com/nsn/5990-00-622-1010>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 1.9990 inches and 1.9995 inches

Pilot Diameter:

Between 0.7495 inches and 0.7500 inches

Overall Length:

3.1720 inches

Flange Diameter:

Between 2.1600 inches and 2.1610 inches

Flange Thickness:

0.1250 inches

Undercut Diameter:

2.0000 inches

Undercut Width:

0.1000 inches

Shaft Diameter:

0.1845 inches single shaft and 0.0470 inches single shaft

Shaft Length:

0.5600 inches single shaft

Body Size:

22

Stator Input Voltage Rating In Volts:

26.0

Stator Input Current Rating:

50.0 amperes

Stator Input Electrical Power Rating:

5.0 watts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

1.50

Zso Resistance In Ohms:

1.30

Rotor Dc Resistance In Ohms:

0.35

Stator Dc Resistance In Ohms:

0.28

Phase Shift Angle In Deg:

2.000 input to output

Electrical Error Angular Range In Minutes:

-15.0/+15.0

Actuator Friction Torque At Minus 55 Deg Celsius:

60.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

20.0 centimeter-grams

Pilot Length:

0.0600 inches

Shoulder Length:

0.2000 inches

Mounting Surface To Terminal End Distance:

2.6120 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

8.80

Shaft Slot Depth:

0.0470 inches single shaft

Plus J Zso Reactance In Ohms:

7.50

Shaft Slot Width:

0.0470 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

1.100 rotor to stator

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800