

View Online at <https://aerobasegroup.com/nsn/5990-00-623-4198>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

2.3200 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1200 inches single shaft

Shaft Length:

0.5550 inches single shaft

Maximum Temperature Rise:

2.0 degrees celsius

Body Size:

11

Stator Input Voltage Rating In Volts:

90.0

Stator Input Current Rating:

20.0 milliamperes

Stator Input Electrical Power Rating:

180.0 milliwatts

Frequency In Hertz:

400.0

Zro Impedance Magnitude In Ohms:

3340.00

Zro Impedance Angle In Deg:

9.20

Zso Impedance Magnitude In Ohms:

5470.00

Zso Impedance Angle In Deg:

80.80

Rotor Dc Resistance In Ohms:

385.00

Stator Dc Resistance In Ohms:

555.00

Phase Shift Angle In Deg:

4.500 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

59.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

94.00

Electrical Error Angular Range In Minutes:

-10.0/+10.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7650 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0310 inches single shaft

Shaft Slot Width:

0.0310 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.735 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800