

View Online at <https://aerobasegroup.com/nsn/5990-00-631-9479>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.8118 inches and 0.8123 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6540 inches

Flange Diameter:

Between 0.9360 inches and 0.9370 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.8350 inches and 0.8400 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0880 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.4130 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

10

Stator Input Voltage Rating In Volts:

10.2

Stator Input Current Rating:

23.0 milliamperes

Stator Input Electrical Power Rating:

70.0 milliwatts

Frequency In Hertz:

400.0

Zso Resistance In Ohms:

126.00

Stator Dc Resistance In Ohms:

126.00

Phase Shift Angle In Deg:

12.000 input to output

Electrical Error Angular Range In Minutes:

-7.5/+7.5

Actuator Friction Torque At Minus 55 Deg Celsius:

20.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Alignment Hole Quantity:

3

Pilot Length:

0.0380 inches

Shoulder Length:

0.0630 inches

Mounting Surface To Terminal End Distance:

1.2790 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0310 inches single shaft

Plus J Zso Reactance In Ohms:

427.00

Shaft Slot Width:

0.0270 inches single shaft

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.0620 inches

Alignment Hole Bolt Circle Diameter:

0.6780 inches

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800