## NSN 5990-00-631-9480

Transmitter Synchro - Page 1 of 3

Between 0.8118 inches and 0.8123 inches

**Body Material:** 

**Pilot Diameter:** 

Aluminum

Body Style:

Standard round c

Shoulder Diameter:



View Online at https://aerobasegroup.com/nsn/5990-00-631-9480

| Between 0.4995 inches and 0.5000 inches                   |
|---|
| Overall Length:   |
| 1.6540 inches   |
| Flange Diameter:  |
| Between 0.9360 inches and 0.9370 inches                   |
| Flange Thickness:   |
| 0.0620 inches   |
| Undercut Diameter:  |
| Between 0.8350 inches and 0.8400 inches                   |
| Undercut Width:   |
| 0.0620 inches   |
| Shaft Diameter:   |
| 0.0880 inches single shaft and 0.0900 inches single shaft |
| Shaft Length:   |
| 0.4130 inches single shaft                                |
| Fragility Factor:   |
| Moderately rugged   |
| Maximum Tempurature Rise:                                 |
| 40.0 degrees celsius                                      |
| Body Size:  |
| 10  |
| Rotor Input Voltage Rating In Volts:                      |
| 26.0  |
| Frequency In Hertz:                                       |
| 400.0   |
| Rotor Input Current Rating:                               |
| 185.0 milliamperes  |
| Rotor Input Electrical Power Rating:                      |
| 1.7 watts   |
| Zro Resistance In Ohms:                                   |
| 35.00   |
| Zso Resistance In Ohms:                                   |
| 10.30   |
| Zrs Resistance In Ohms:                                   |
| 66.00   |
|   |
|   |

## NSN 5990-00-631-9480

Transmitter Synchro - Page 2 of 3



| Zso-9 Designator Resistance In Ohms:              |
|---|
| 9.10  |
| Rotor Dc Resistance In Ohms:                      |
| 26.00   |
| Stator Dc Resistance In Ohms:                     |
| 10.90   |
| Electrical Error Angular Range In Minutes:        |
| -2.0/+2.0   |
| Actuator Friction Torque At Minus 55 Deg Celsius: |
| 15.0 centimeter-grams                             |
| Actuator Friction Torque At Plus 25 Deg Celsius:  |
| 4.0 centimeter-grams                              |
| Torque Gradient Per Angular Deg:                  |
| 2250.0 millimeter-milligrams                      |
| Alignment Hole Quantity:                          |
| 3   |
| Pilot Length:                                     |
| 0.0380 inches                                     |
| Shoulder Length:                                  |
| 0.0630 inches                                     |
| Mounting Surface To Terminal End Distance:        |
| 1.2030 inches                                     |
| Terminal Location:                                |
| Rear  |
| Plus J Zro Reactance In Ohms:                     |
| 145.00  |
| Shaft Slot Depth:                                 |
| 0.0210 inches single shaft                        |
| Plus J Zso Reactance In Ohms:                     |
| 31.00   |
| Shaft Slot Width:                                 |
| 0.0200 inches single shaft                        |
| Plus J Zrs Reactance In Ohms:                     |
| 27.50   |
| Shaft Type:                                       |
| Round, slotted single shaft                       |
| Alignment Hole Depth:                             |
| 0.0630 inches                                     |
| Alignment Hole Bolt Circle Diameter:              |
| 0.6780 inches                                     |
| Plus J Zso-9 Designator Reactance In Ohms:        |
| 10.70   |
| Terminal Type And Quantity:                       |

5 wire lead

## NSN 5990-00-631-9480

Transmitter Synchro - Page 3 of 3



|  |  | ife: |  |
|--|--|------|--|
|  |  |      |  |
|  |  |      |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A07800