NSN 5990-00-636-4111

Receiver Synchro - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5990-00-636-4111

Body Material:

Steel, stainless

Body Style:

Standard round d

Shoulder Diameter:

Between 1.9850 inches and 1.9900 inches

Pilot Diameter:

Between 0.5900 inches and 0.6000 inches

Second Shoulder Diameter:

Between 1.9985 inches and 1.9995 inches

Second Shoulder Length:

Between 0.1680 inches and 0.1700 inches

Overall Length:

4.2940 inches

Flange Diameter:

Between 2.2490 inches and 2.2500 inches

Flange Thickness:

Between 0.2480 inches and 0.2500 inches

Body Diameter:

Between 1.9850 inches and 1.9900 inches

Shaft Diameter:

0.2402 inches single shaft and 0.2405 inches single shaft

Shaft Length:

0.6930 inches single shaft and 0.7190 inches single shaft

Maximum Tempurature Rise:

65.0 degrees celsius

Body Size:

23

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

945.0 milliamperes

Rotor Input Electrical Power Rating:

7.8 watts

Zro Resistance In Ohms:

9.10

Zso Resistance In Ohms:

8.20

Zrs Resistance In Ohms:

12.00

NSN 5990-00-636-4111

Receiver Synchro - Page 2 of 3



Zso-9 Designator Resistance In Ohms: 6.16 Maximum Fundamental Null Voltage In Millivolts Per Volt: 75.00 output Maximum Total Null Voltage Output In Millivolts Per Volt: 100.00 **Electrical Error Angular Range In Minutes:** -8.0/+8.0 **Receiver Error Angular Range In Minutes:** -60.0/+60.0 **Torque Gradient Per Angular Deg:** 0.130 inch-ounces **Alignment Hole Quantity:** 3 Pilot Length: Between 0.0360 inches and 0.0460 inches **Shoulder Length:** 0.2500 inches Aft Of First Flange Diameter: Between 1.9985 inches and 1.9995 inches **Mounting Surface To Terminal End Distance:** 3.4450 inches **Shaft Thread Series Designator:** Unf single shaft **Shaft Thread Direction:** Right-hand single shaft **Shaft Thread Class:** 2a single shaft **Terminal Location:** Rear **Shaft Thread Length:** 0.3100 inches single shaft and 0.3300 inches single shaft Plus J Zro Reactance In Ohms: 119.00 Plus J Zso Reactance In Ohms: 61.50 Plus J Zrs Reactance In Ohms: 9.62 **Shaft Type:** Round, threaded single shaft Alignment Hole Depth:

0.783 rotor to stator

Transformation Ratio:

0.1250 inches

NSN 5990-00-636-4111Receiver Synchro - Page 3 of 3

Fiig: A07800



Alignment Hole Bolt Circle Diameter:
1.6420 inches
Plus J Zso-9 Designator Reactance In Ohms:
21.70
Shaft Thread Size:
0.250 inches single shaft
Special Features:
Slotted keyway full length of shaft
Test Data Document:
81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
5 screw
Specification Data:
81349-mil-s-20708/94 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli