

View Online at <https://aerobasegroup.com/nsn/5990-00-636-4119>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round d

Shoulder Diameter:

1.9900 inches

Pilot Diameter:

0.5950 inches

Second Shoulder Diameter:

1.9920 inches

Second Shoulder Length:

0.2500 inches

Overall Length:

4.2790 inches

Flange Diameter:

2.2500 inches

Flange Thickness:

0.4200 inches

Body Diameter:

2.2500 inches

Shaft Diameter:

0.2405 inches single shaft

Shaft Length:

0.6560 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

23

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

264.0 milliamperes

Rotor Input Electrical Power Rating:

3.0 watts

Pilot Length:

0.0430 inches

Shoulder Length:

0.0170 inches

Aft Of First Flange Diameter:

1.9995 inches

Mounting Surface To Terminal End Distance:

3.1600 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0500 inches single shaft

Shaft Slot Width:

0.0620 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.783 rotor to stator

Test Data Document:

81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 screw

Specification Data:

81349-mil-s-20708/94b government specification

Specification Or Standard:

23cx4 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800