#### NSN 5990-00-644-0088

Differential Transmitter Synchro - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5990-00-644-0088 **Body Material:** Aluminum **Body Style:** Standard round double flange a **Shoulder Diameter:** 4.8740 inches **Pilot Diameter:** 1.7500 inches **Second Shoulder Diameter:** 5.5000 inches **Second Shoulder Length:** 0.5000 inches **Overall Length:** 9.2100 inches Flange Diameter: Between 5.7480 inches and 5.7500 inches Flange Thickness: Between 0.2450 inches and 0.2500 inches **Body Diameter:** 5.3750 inches **Shaft Diameter:** 0.3500 inches single shaft and 0.3505 inches single shaft **Shaft Length:** 1.0320 inches single shaft **Shaft Undercut Width:** 0.0600 inches single shaft **Distance Between Flanges:** 3.2500 inches **Maximum Tempurature Rise:** 50.0 degrees celsius **Body Size: Stator Input Voltage Rating In Volts:** 115.0 **Stator Input Current Rating:** 3.5 amperes **Stator Input Electrical Power Rating:** 

30.0 watts

Frequency In Hertz:

**Zro Resistance In Ohms:** 

400.00

60.0

#### NSN 5990-00-644-0088

Differential Transmitter Synchro - Page 2 of 3



### **Electrical Error Angular Range In Minutes:** -18.0/+18.0 **Torque Gradient Per Angular Deg:** 4.000 inch-ounces Pilot Length: 0.2500 inches **Shoulder Length:** 1.0600 inches Aft Of Second Flange Diameter: 4.8750 inches **Mounting Surface To Terminal End Distance:** 6.6180 inches **Shaft Thread Series Designator:** Unf single shaft **Shaft Thread Direction:** Right-hand single shaft **Shaft Thread Class:** 2a **Terminal Location:** Rear Plus J Zro Reactance In Ohms: 660.00 **Shaft Tapered End Minor Diameter:** 0.2500 inches single shaft **Shaft Type:** Round, tapered, threaded, undercut single shaft **Transformation Ratio:** 0.990 rotor to stator Shaft Taper Angle In Deg: 3.5 single shaft **Shaft Tip Length:** 0.2200 inches single shaft **Shaft Taper Length:** 0.3750 inches single shaft **Shaft Thread Size:** 0.250 inches single shaft **Shaft Undercut Diameter:** 0.0600 inches single shaft **Special Features:** Shaft keyed with no. 00 woodruff keywhitney no. 207

## Test Data Document:

81349-mil-s-2335 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### Terminal Type And Quantity:

# NSN 5990-00-644-0088

Differential Transmitter Synchro - Page 3 of 3



Sı	oec	ific	cati	on	Data:

81349-mil-s-2335 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800