

View Online at <https://aerobasegroup.com/nsn/5990-00-644-0100>

Body Material:

Aluminum

Body Style:

Standard round d

Shoulder Diameter:

Between 1.9890 inches and 1.9900 inches

Pilot Diameter:

0.9950 inches

Second Shoulder Diameter:

Between 1.9990 inches and 1.9995 inches

Second Shoulder Length:

0.1700 inches

Overall Length:

4.5490 inches

Flange Diameter:

Between 2.2490 inches and 2.2500 inches

Flange Thickness:

0.2500 inches

Body Diameter:

1.9900 inches

Shaft Diameter:

0.2400 inches single shaft and 0.2405 inches single shaft

Shaft Length:

0.7190 inches single shaft

Maximum Temperature Rise:

25.0 degrees celsius

Body Size:

23

Stator Input Voltage Rating In Volts:

115.0

Stator Input Current Rating:

297.0 milliamperes

Stator Input Electrical Power Rating:

4.0 watts

Frequency In Hertz:

400.0

Maximum Fundamental Null Voltage In Millivolts Per Volt:

50.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

100.00

Electrical Error Angular Range In Minutes:

-8.0/+8.0

Spline Tooth Quantity:

22 single shaft

Actuator Friction Torque At Minus 55 Deg Celsius:

0.50 inch-ounces

Actuator Friction Torque At Plus 25 Deg Celsius:

0.20 inch-ounces

Pilot Length:

0.0430 inches

Shoulder Length:

0.2500 inches

Aft Of First Flange Diameter:

Between 1.9990 inches and 1.9995 inches

Mounting Surface To Terminal End Distance:

2.9040 inches

Spline Tooth Diametral Pitch:

96 single shaft

Shaft Thread Series Designator:

Unf single shaft

Shaft Thread Direction:

Right-hand single shaft

Shaft Thread Class:

2a

Terminal Location:

Rear

Shaft Thread Length:

0.2900 inches single shaft

Shaft Type:

Spline w/threads single shaft

Transformation Ratio:

1.154 rotor to stator

Shaft Thread Size:

0.240 inches single shaft

Test Data Document:

81349-mil-s-16892 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

7 screw

Specification Data:

81349-mil-s-16892 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

N/A

Fig:

A07800