NSN 5990-00-644-0102

Differential Transmitter Synchro - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5990-00-644-01
Body Material:
Steel, stainless
Body Style:
Standard round d
Shoulder Diameter:
Between 1.9850 inches and 1.9900 inches
Pilot Diameter:
Between 0.5900 inches and 0.6000 inches
Second Shoulder Diameter:
Between 1.9985 inches and 1.9995 inches
Second Shoulder Length:
Between 0.1680 inches and 0.1700 inches
Overall Length:
4.5440 inches
Flange Diameter:
Between 2.2490 inches and 2.2500 inches
Flange Thickness:
0.2500 inches
Body Diameter:
Between 1.9850 inches and 1.9900 inches
Shaft Diameter:
0.2395 inches single shaft and 0.2405 inches single shaft
Shaft Length:
0.6930 inches single shaft and 0.7190 inches single shaft
Maximum Tempurature Rise:
45.0 degrees celsius
Body Size:
23
Stator Input Voltage Rating In Volts:
90.0
Stator Input Current Rating:
112.0 milliamperes
Stator Input Electrical Power Rating:
2.2 watts
Frequency In Hertz:
60.0
Zro Resistance In Ohms:
330.00
Zso Resistance In Ohms:
211.00
Zrs Resistance In Ohms:

471.00

NSN 5990-00-644-0102

Differential Transmitter Synchro - Page 2 of 3



Maximum Fundamental Null Voltage In Millivolts Per Volt: 75.00 output Maximum Total Null Voltage Output In Millivolts Per Volt: 100.00 **Electrical Error Angular Range In Minutes:** -8.0/+8.0 **Spline Tooth Quantity:** 22 single shaft **Actuator Friction Torque At Minus 55 Deg Celsius:** 0.50 inch-ounces **Actuator Friction Torque At Plus 25 Deg Celsius:** 0.20 inch-ounces **Pilot Length:** Between 0.0360 inches and 0.0460 inches **Shoulder Length:** Between 0.2460 inches and 0.2520 inches Aft Of First Flange Diameter: Between 1.9985 inches and 1.9995 inches **Mounting Surface To Terminal End Distance:** 3.4450 inches **Spline Tooth Diametral Pitch:** 96 single shaft **Shaft Thread Series Designator:** Unf single shaft **Shaft Thread Direction:** Right-hand single shaft **Shaft Thread Class:** 2a **Terminal Location:** Rear **Shaft Thread Length:** 0.2500 inches single shaft Plus J Zro Reactance In Ohms: 1006.00 Plus J Zso Reactance In Ohms: 757.00 Plus J Zrs Reactance In Ohms:

127.00

Shaft Type:

Spline w/threads single shaft

Transformation Ratio:

1.154 rotor to stator

Shaft Thread Size:

0.250 inches single shaft

NSN 5990-00-644-0102

Differential Transmitter Synchro - Page 3 of 3



Test Data Document:

81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

7 screw

Specification Data:

81349-mil-s-20708/94 government specification

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A07800