

View Online at <https://aerobasegroup.com/nsn/5990-00-655-2379>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 1.3115 inches and 1.3120 inches

Pilot Diameter:

Between 0.8745 inches and 0.8750 inches

Overall Length:

2.4790 inches

Flange Diameter:

Between 1.4360 inches and 1.4370 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

1.3120 inches

Undercut Width:

0.0780 inches

Shaft Diameter:

0.1870 inches single shaft

Shaft Length:

0.5400 inches single shaft

Body Size:

15

Stator Input Voltage Rating In Volts:

60.0

Stator Input Current Rating:

45.0 milliamperes

Frequency In Hertz:

400.0

Rotor Dc Resistance In Ohms:

200.00

Stator Dc Resistance In Ohms:

295.00

Compensation Method:

Winding compensated

Compensator Dc Resistance In Ohms:

295.00

Phase Shift Angle In Deg:

6.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

20.00

Electrical Error Angular Range In Minutes:

-5.0/+5.0

Spline Tooth Quantity:

21 single shaft

Alignment Hole Quantity:

4

Pilot Length:

0.0400 inches

Shoulder Length:

0.1320 inches

Mounting Surface To Terminal End Distance:

1.9540 inches

Spline Tooth Diametral Pitch:

120 single shaft

Terminal Location:

Rear

Shaft Type:

Spline single shaft

Alignment Hole Depth:

0.1250 inches

Transformation Ratio:

0.980 rotor to stator

Alignment Hole Bolt Circle Diameter:

1.0000 inches

Terminal Type And Quantity:

12 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800