NSN 5990-00-655-2436

Control Transformer Synchro - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5990-00-655-2436



Body Material: Steel, stainless **Body Style:** Standard round a **Pilot Diameter:** Between 0.4995 inches and 0.5000 inches **Overall Length:** 1.6160 inches Flange Diameter: 0.7500 inches Flange Thickness: 0.0620 inches **Undercut Diameter:** Between 0.6880 inches and 0.6910 inches **Undercut Width:** 0.0620 inches **Shaft Diameter:** 0.4995 inches single shaft and 0.5000 inches single shaft **Shaft Length:** 0.3750 inches single shaft **Fragility Factor:** Moderately rugged **Maximum Tempurature Rise:** 3.0 degrees celsius **Body Size: Stator Input Voltage Rating In Volts: Stator Input Current Rating:** 37.0 milliamperes **Stator Input Electrical Power Rating:** 100.0 milliwatts Frequency In Hertz: 400.0 **Zro Resistance In Ohms:** 470.00 **Zso Resistance In Ohms:** 81.00 **Zrs Resistance In Ohms:** 590.00 **Rotor Dc Resistance In Ohms:** 381.00

NSN 5990-00-655-2436 Control Transformer Synchro - Page 2 of 2



Stator Dc Resistance In Ohms:
Between 48.00 and 73.00
Phase Shift Angle In Deg:
9.200 input to output
Electrical Error Angular Range In Minutes:
-15.0/+15.0
Actuator Friction Torque At Minus 55 Deg Celsius:
9.0 centimeter-grams
Actuator Friction Torque At Plus 25 Deg Celsius:
3.0 centimeter-grams
Pilot Length:
0.0430 inches
Mounting Surface To Terminal End Distance:
1.2410 inches
Terminal Location:
Rear
Plus J Zro Reactance In Ohms:
1770.00
Shaft Slot Depth:
0.0300 inches single shaft
Plus J Zso Reactance In Ohms:
330.00
Shaft Slot Width:
0.0250 inches single shaft
Plus J Zrs Reactance In Ohms:
190.00
Shaft Type:
Round, slotted single shaft
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A07800