

View Online at <https://aerobasegroup.com/nsn/5990-00-655-2440>

Body Material:

Steel, stainless

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6160 inches

Flange Diameter:

Between 0.7490 inches and 0.7500 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.6880 inches and 0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.3750 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

8

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

100.0 milliamperes

Rotor Input Electrical Power Rating:

540.0 milliwatts

Zro Resistance In Ohms:

54.00

Zso Resistance In Ohms:

12.00

Zrs Resistance In Ohms:

80.00

Rotor Dc Resistance In Ohms:

37.00

Stator Dc Resistance In Ohms:

12.00

Receiver Error Angular Range In Minutes:

-15.0/+15.0

Actuator Friction Torque At Minus 55 Deg Celsius:

5400.0 millimeter-milligrams

Actuator Friction Torque At Plus 25 Deg Celsius:

2700.0 millimeter-milligrams

Torque Gradient Per Angular Deg:

2200.0 millimeter-milligrams

Pilot Length:

0.0430 inches

Mounting Surface To Terminal End Distance:

1.2410 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

260.00

Plus J Zso Reactance In Ohms:

45.00

Plus J Zrs Reactance In Ohms:

20.00

Shaft Type:

Round single shaft

Transformation Ratio:

0.454 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800