

View Online at <https://aerobasegroup.com/nsn/5990-00-655-2705>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 1.3115 inches and 1.3120 inches

Pilot Diameter:

Between 0.8745 inches and 0.8750 inches

Overall Length:

Between 2.6320 inches and 2.6380 inches

Flange Diameter:

Between 1.4360 inches and 1.4370 inches

Flange Thickness:

Between 0.0900 inches and 0.0960 inches

Undercut Diameter:

Between 1.3090 inches and 1.3150 inches

Undercut Width:

Between 0.0730 inches and 0.0830 inches

Shaft Diameter:

0.1870 inches single shaft and 0.1873 inches single shaft

Shaft Length:

0.5680 inches single shaft and 0.5740 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

15

Stator Input Voltage Rating In Volts:

23.0

Frequency In Hertz:

1000.0

Compensation Method:

Winding compensated

Maximum Fundamental Null Voltage In Millivolts Per Volt:

20.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

300.00

Alignment Hole Quantity:

4

Pilot Length:

Between 0.0370 inches and 0.0430 inches

Shoulder Length:

Between 0.1299 inches and 0.1350 inches

Mounting Surface To Terminal End Distance:

1.9540 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0300 inches single shaft

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.1250 inches

Transformation Ratio:

1.000 rotor to stator

Alignment Hole Bolt Circle Diameter:

Between 1.0970 inches and 1.1030 inches

Terminal Type And Quantity:

12 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800