## NSN 5990-00-660-8883

Transmitter Synchro - Page 1 of 2



View Onlin	e at https://aerobasegroup.com/nsn/5990-00-660-8883
Body Mate	erial:
Steel, corr	osion resisting
Body Style	e:
Standard ro	ound double flange b
Shoulder I	Diameter:
3.3900 incl	nes
Pilot Diam	eter:
1.6300 incl	nes
Overall Le	ngth:
6.0500 incl	nes
Flange Dia	imeter:
Between 3.	6230 inches and 3.6250 inches
Flange Thi	ckness:
Between 0.	2450 inches and 0.2500 inches
Shaft Dian	neter:
0.2498 incl	nes single shaft and 0.2500 inches single shaft
Shaft Leng	gth:
0.9900 incl	nes single shaft
Distance E	Between Flanges:
1.8120 inch	nes
Maximum	Tempurature Rise:
50.0 degre	es celsius
Body Size	:
37	
Rotor Inpu	t Voltage Rating In Volts:
115.0	
Frequency	n Hertz:
60.0	
Rotor Inpu	it Current Rating:

600.0 milliamperes

**Rotor Input Electrical Power Rating:** 

**Electrical Error Angular Range In Minutes:** 

-18.0/+18.0

**Torque Gradient Per Angular Deg:** 

0.400 inch-ounces

Pilot Length:

0.1600 inches

**Shoulder Length:** 

1.0300 inches

**Shaft Thread Series Designator:** 

Unf single shaft

## **NSN 5990-00-660-8883** Transmitter Synchro - Page 2 of 2



Shaft Thread Direction:
Right-hand single shaft
Shaft Thread Class:
2b single shaft
Terminal Location:
Rear
Shaft Thread Length:
0.1870 inches single shaft
Plus J Zro Reactance In Ohms:
0.187
Shaft Type:
Round, threaded single shaft
Transformation Ratio:
1.710 stator to rotor
Shaft Thread Size:
0.2500 inches single shaft
Terminal Type And Quantity:
5 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A07800