

View Online at <https://aerobasegroup.com/nsn/5990-00-673-1831>

Body Material:

Aluminum

Body Style:

Standard round b

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

2.1390 inches

Flange Diameter:

Between 1.0590 inches and 1.0620 inches

Flange Thickness:

0.0930 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3740 inches single shaft

Maximum Temperature Rise:

15.0 degrees celsius

Body Size:

11

Rotor Input Voltage Rating In Volts:

115.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

60.0 milliamperes

Rotor Input Electrical Power Rating:

1.0 watts

Zro Impedance Magnitude In Ohms:

2210.00

Zro Impedance Angle In Deg:

82.30

Zso Impedance Magnitude In Ohms:

1130.00

Zso Impedance Angle In Deg:

81.30

Rotor Dc Resistance In Ohms:

159.00

Stator Dc Resistance In Ohms:

137.00

Phase Shift Angle In Deg:

40.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

59.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

94.00

Electrical Error Angular Range In Minutes:

-10.0/+10.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.00 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7030 inches

Terminal Location:

Rear

Shaft Type:

Round single shaft

Transformation Ratio:

0.783 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800