

View Online at <https://aerobasegroup.com/nsn/5990-00-677-6476>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round b

Shoulder Diameter:

Between 1.3115 inches and 1.3120 inches

Pilot Diameter:

Between 0.8745 inches and 0.8750 inches

Overall Length:

3.1330 inches

Flange Diameter:

Between 1.5320 inches and 1.5410 inches

Flange Thickness:

Between 0.0900 inches and 0.0960 inches

Undercut Width:

Between 0.0730 inches and 0.0830 inches

Shaft Diameter:

0.1870 inches single shaft and 0.1872 inches single shaft

Shaft Length:

2.6330 inches single shaft

Body Size:

16

Stator Input Voltage Rating In Volts:

115.0

Stator Input Current Rating:

24.0 milliamperes

Stator Input Electrical Power Rating:

600.0 milliwatts

Frequency In Hertz:

400.0

Phase Shift Angle In Deg:

8.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

40.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

60.00

Electrical Error Angular Range In Minutes:

-10.0/+10.0

Spline Tooth Quantity:

21 single shaft

Torque Gradient Per Angular Deg:

0.050 inch-ounces

Pilot Length:

Between 0.0370 inches and 0.0430 inches

Shoulder Length:

Between 0.1270 inches and 0.1370 inches

Mounting Surface To Terminal End Distance:

Between 2.5775 inches and 2.5780 inches

Spline Tooth Diametral Pitch:

120 single shaft

Shaft Thread Series Designator:

Unf single shaft

Shaft Thread Direction:

Right-hand single shaft

Shaft Thread Class:

2a

Terminal Location:

Rear

Shaft Thread Length:

0.2000 inches single shaft

Shaft Type:

Spline w/threads single shaft

Transformation Ratio:

0.735 rotor to stator

Shaft Thread Size:

0.184 inches single shaft

Test Data Document:

81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

5 screw

Specification Data:

81349-mil-s-20708/25 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800