

View Online at <https://aerobasegroup.com/nsn/5990-00-677-6480>

**Body Material:**

Steel, stainless

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 1.5615 inches and 1.5620 inches

**Pilot Diameter:**

Between 0.9370 inches and 0.9375 inches

**Overall Length:**

3.2050 inches

**Flange Diameter:**

Between 1.7450 inches and 1.7500 inches

**Flange Thickness:**

0.0930 inches

**Undercut Diameter:**

1.6250 inches

**Undercut Width:**

0.0780 inches

**Shaft Diameter:**

0.1870 inches single shaft and 0.1872 inches single shaft

**Shaft Length:**

0.5400 inches single shaft

**Maximum Temperature Rise:**

20.0 degrees celsius

**Body Size:**

18

**Stator Input Voltage Rating In Volts:**

90.0

**Stator Input Current Rating:**

450.0 milliamperes

**Stator Input Electrical Power Rating:**

4.5 watts

**Frequency In Hertz:**

400.0

**Zso Impedance Magnitude In Ohms:**

Between 178.00 and 266.00

**Zso Impedance Angle In Deg:**

Between 83.00 and 87.00

**Zrs Impedance Magnitude In Ohms:**

Between 26.00 and 38.00

**Zrs Impedance Angle In Deg:**

Between 47.00 and 56.00

**Phase Shift Angle In Deg:**

3.000 input to output

**Electrical Error Angular Range In Minutes:**

-8.0/+8.0

**Spline Tooth Quantity:**

21 single shaft

**Actuator Friction Torque At Minus 55 Deg Celsius:**

0.10 inch-ounces

**Torque Gradient Per Angular Deg:**

0.060 inch-ounces

**Pilot Length:**

0.0400 inches

**Shoulder Length:**

0.1320 inches

**Mounting Surface To Terminal End Distance:**

2.6700 inches

**Spline Tooth Diametral Pitch:**

120 single shaft

**Shaft Thread Series Designator:**

Unf single shaft

**Shaft Thread Direction:**

Right-hand single shaft

**Shaft Thread Class:**

2a

**Terminal Location:**

Rear

**Shaft Thread Length:**

0.2000 inches single shaft

**Shaft Type:**

Spline w/threads single shaft

**Transformation Ratio:**

1.154 rotor to stator

**Shaft Thread Size:**

0.190 inches single shaft

**Test Data Document:**

81349-mil-s-20708 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

6 screw

**Specification Data:**

81349-mil-s-20708/31 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A07800