## NSN 5990-00-681-2726

Transmitter Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-681-2726

Body Material:
Aluminum
Body Style:
Standard round c
Shoulder Diameter:
Between 1.3115 inches and 1.3120 inches
Pilot Diameter:
Between 0.4995 inches and 0.5000 inches
Overall Length:
1.1310 inches
Flange Diameter:
Between 1.4360 inches and 1.4370 inches
Flange Thickness:
0.0930 inches
Undercut Diameter:
1.3120 inches
Undercut Width:
0.0780 inches
Shaft Diameter:
0.1195 inches single shaft and 0.1200 inches single shaft
Shaft Length:
0.1200 inches single shaft
Body Size:
15
Rotor Input Voltage Rating In Volts:
26.0
Frequency In Hertz:
400.0
Rotor Input Current Rating:
125.0 milliamperes
Rotor Input Electrical Power Rating:
600.0 milliwatts
Zro Resistance In Ohms:
33.00
Zso Resistance In Ohms:
9.40
Zrs Resistance In Ohms:
36.00
Rotor Dc Resistance In Ohms:
12.60
Stator Dc Resistance In Ohms:

5.80

## **NSN 5990-00-681-2726** Transmitter Synchro - Page 2 of 2



Phase Shift Angle In Deg:
2.700 input to output
Electrical Error Angular Range In Minutes:
-12.0/+12.0
Alignment Hole Quantity:
4
Pilot Length:
0.0400 inches
Shoulder Length:
0.1320 inches
Mounting Surface To Terminal End Distance:
1.5910 inches
Terminal Location:
Rear
Plus J Zro Reactance In Ohms:
224.00
Shaft Slot Depth:
0.0210 inches single shaft and 0.0310 inches single shaft
Plus J Zso Reactance In Ohms:
39.00
Shaft Slot Width:
0.0210 inches single shaft and 0.0310 inches single shaft
Plus J Zrs Reactance In Ohms:
22.50
Shaft Type:
Round, slotted single shaft
Alignment Hole Depth:
0.1250 inches
Alignment Hole Bolt Circle Diameter:
0.8750 inches
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A07800