

View Online at <https://aerobasegroup.com/nsn/5990-00-682-9897>

Body Material:

Aluminum alloy

Body Style:

Standard round c

Shoulder Diameter:

Between 0.8118 inches and 0.8123 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6160 inches

Flange Diameter:

Between 0.9360 inches and 0.9370 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.8370 inches and 0.8400 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.2405 inches single shaft

Shaft Length:

0.7000 inches single shaft

Body Size:

10

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

145.0 milliamperes

Rotor Input Electrical Power Rating:

660.0 milliwatts

Zro Resistance In Ohms:

32.00

Zso Resistance In Ohms:

7.50

Zrs Resistance In Ohms:

47.00

Rotor Dc Resistance In Ohms:

16.60

Stator Dc Resistance In Ohms:

7.30

Phase Shift Angle In Deg:

5.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-30.0/+30.0

Alignment Hole Quantity:

3

Pilot Length:

0.0380 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.2410 inches

Terminal Location:

Rear

Shaft Thread Length:

0.3100 inches single shaft

Plus J Zro Reactance In Ohms:

180.00

Shaft Slot Depth:

0.0250 inches single shaft and 0.0300 inches single shaft

Plus J Zso Reactance In Ohms:

31.00

Shaft Slot Width:

0.0150 inches single shaft and 0.0200 inches single shaft

Plus J Zrs Reactance In Ohms:

16.00

Shaft Type:

Round, slotted single shaft

Alignment Hole Depth:

0.0500 inches

Transformation Ratio:

0.783 rotor to stator

Alignment Hole Bolt Circle Diameter:

0.5000 inches

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800