

View Online at <https://aerobasegroup.com/nsn/5990-00-683-0531>

Body Material:

Steel, stainless

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

Between 2.1290 inches and 2.1530 inches

Flange Diameter:

Between 1.0570 inches and 1.0650 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3640 inches single shaft and 0.3880 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

20.0 milliamperes

Rotor Input Electrical Power Rating:

80.0 milliwatts

Zro Impedance Magnitude In Ohms:

1580.00

Zro Impedance Angle In Deg:

78.50

Zso Impedance Magnitude In Ohms:

1300.00

Zso Impedance Angle In Deg:

78.00

Transformation Ratio Equality In Percent:

4.0

Phase Shift Angle In Deg:

7.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

29.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

46.00

Electrical Error Angular Range In Minutes:

-5.0/+5.0

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.7650 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

0.846 rotor to stator

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800