

View Online at <https://aerobasegroup.com/nsn/5990-00-683-1014>

**Body Material:**

Steel, stainless

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.9995 inches and 1.0000 inches

**Pilot Diameter:**

0.6250 inches

**Overall Length:**

2.2380 inches

**Flange Diameter:**

1.0620 inches

**Flange Thickness:**

0.0930 inches

**Undercut Diameter:**

0.9800 inches

**Undercut Width:**

0.0500 inches

**Shaft Diameter:**

0.1195 inches single shaft and 0.1200 inches single shaft

**Shaft Length:**

0.3760 inches single shaft

**Body Size:**

11

**Stator Input Voltage Rating In Volts:**

11.8

**Stator Input Current Rating:**

165.0 milliamperes

**Stator Input Electrical Power Rating:**

250.0 milliwatts

**Frequency In Hertz:**

400.0

**Zro Impedance Magnitude In Ohms:**

418.00

**Zro Impedance Angle In Deg:**

78.30

**Zso Impedance Magnitude In Ohms:**

74.30

**Zso Impedance Angle In Deg:**

79.70

**Zrs Impedance Magnitude In Ohms:**

104.00

**Zrs Impedance Angle In Deg:**

26.80

**Rotor Dc Resistance In Ohms:**

62.10

**Stator Dc Resistance In Ohms:**

10.00

**Phase Shift Angle In Deg:**

6.000 input to output

**Maximum Fundamental Null Voltage In Millivolts Per Volt:**

30.00 output

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

40.00

**Electrical Error Angular Range In Minutes:**

-7.0/+7.0

**Actuator Friction Torque At Minus 55 Deg Celsius:**

16.0 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

4.0 centimeter-grams

**Pilot Length:**

0.0620 inches

**Shoulder Length:**

0.0620 inches

**Mounting Surface To Terminal End Distance:**

1.8620 inches

**Terminal Location:**

Rear

**Shaft Slot Depth:**

0.0300 inches single shaft

**Shaft Slot Width:**

0.0250 inches single shaft

**Shaft Type:**

Round, slotted single shaft

**Transformation Ratio:**

2.203 rotor to stator

**Terminal Type And Quantity:**

5 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A07800