

View Online at <https://aerobasegroup.com/nsn/5990-00-686-4446>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

Between 0.8118 inches and 0.8123 inches

Pilot Diameter:

0.5000 inches

Overall Length:

1.9120 inches

Flange Diameter:

0.9370 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.8350 inches and 0.8400 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.4130 inches single shaft

Body Size:

10

Stator Input Voltage Rating In Volts:

11.8

Stator Input Current Rating:

12.0 milliamperes

Stator Input Electrical Power Rating:

50.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

595.00

Zso Resistance In Ohms:

126.00

Zrs Resistance In Ohms:

750.00

Rotor Dc Resistance In Ohms:

410.00

Stator Dc Resistance In Ohms:

126.00

Phase Shift Angle In Deg:

11.000 input to output

Electrical Error Angular Range In Minutes:

-15.0/+15.0

Actuator Friction Torque At Minus 55 Deg Celsius:

20.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.00 centimeter-grams

Alignment Hole Quantity:

3

Pilot Length:

0.0380 inches

Shoulder Length:

0.0630 inches

Mounting Surface To Terminal End Distance:

1.2490 inches

Terminal Location:

Side

Plus J Zro Reactance In Ohms:

2130.00

Shaft Slot Depth:

0.0320 inches single shaft

Plus J Zso Reactance In Ohms:

427.00

Shaft Slot Width:

0.0320 inches single shaft

Plus J Zrs Reactance In Ohms:

369.00

Shaft Type:

Round, slotted front shaft

Alignment Hole Depth:

0.0500 inches

Alignment Hole Bolt Circle Diameter:

0.6780 inches

Special Features:

Rear shaft dim. 0.2500 in. Nom lg, 0.0895 in. Min. 0.0900 in. Maximum lg

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A07800