

NSN 5990-00-686-4631 Transmitter Synchro - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5990-00-686-4631 **Body Material:** Aluminum **Body Style:** Standard round c **Shoulder Diameter:** Between 0.9995 inches and 1.0000 inches **Pilot Diameter:** Between 0.6245 inches and 0.6250 inches **Overall Length:** 1.9950 inches Flange Diameter: Between 1.0590 inches and 1.0620 inches Flange Thickness: 0.0930 inches **Undercut Diameter:** 0.9750 inches **Undercut Width:** 0.0500 inches **Shaft Diameter:** 0.0800 inches single shaft and 0.0810 inches single shaft **Shaft Length:** 0.3130 inches single shaft **Shaft Undercut Width:** 0.0300 inches single shaft **Body Size:** 11 **Rotor Input Voltage Rating In Volts:** 26.0 Frequency In Hertz:

400.0

Rotor Input Current Rating:

120.0 milliamperes

Rotor Input Electrical Power Rating:

600.0 milliwatts

Torque Gradient Per Angular Deg:

2000.000 millimeter-milligrams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.6200 inches

NSN 5990-00-686-4631 Transmitter Synchro - Page 2 of 2



Shaft Thread Series Designator:
Unf single shaft
Shaft Thread Direction:
Right-hand single shaft
Shaft Thread Class:
3a single shaft
Terminal Location:
Rear
Shaft Tapered End Minor Diameter:
0.0600 inches single shaft
Shaft Type:
Round, tapered, threaded, undercut single shaft
Transformation Ratio:
0.454 stator to rotor
Shaft Taper Angle In Deg:
3.0 single shaft
Shaft Tip Length:
0.0630 inches single shaft
Shaft Taper Length:
0.1160 inches single shaft
Shaft Thread Size:
0.0600 inches single shaft
Shaft Undercut Diameter:
0.0450 inches single shaft
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A07800