

View Online at <https://aerobasegroup.com/nsn/5990-00-686-5277>

Body Material:

Aluminum

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

2.0560 inches

Flange Diameter:

Between 1.0590 inches and 1.0620 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.9620 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.1200 inches single shaft

Shaft Length:

0.3740 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

70.0 milliamperes

Rotor Input Electrical Power Rating:

500.0 milliwatts

Zro Resistance In Ohms:

73.00

Zso Resistance In Ohms:

16.60

Zrs Resistance In Ohms:

79.00

Rotor Dc Resistance In Ohms:

35.00

Stator Dc Resistance In Ohms:

12.10

Phase Shift Angle In Deg:

4.500 input to output

Electrical Error Angular Range In Minutes:

-10.0/+10.0

Actuator Friction Torque At Minus 55 Deg Celsius:

9.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.6820 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

420.00

Shaft Slot Depth:

0.0300 inches single shaft

Plus J Zso Reactance In Ohms:

76.00

Shaft Slot Width:

0.0250 inches single shaft

Plus J Zrs Reactance In Ohms:

57.00

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A07800