NSN 5990-00-688-4759 Control Transformer Synchro - Page 1 of 2



View On	line at https://aerobasegroup.com/nsn/5990-00-688-4759
Body Ma	aterial:
Steel, co	orrosion resisting
Body St	yle:
Standard	d round a
Pilot Dia	ameter:
Between	0.4995 inches and 0.5000 inches
Overall	Length:
1.6160 in	nches
Flange I	Diameter:
Between	0.7490 inches and 0.7500 inches
Flange	Thickness:
0.0620 in	nches
Undercu	ut Diameter:
Between	0.6880 inches and 0.6910 inches
Undercu	ut Width:
0.0620 in	nches
Shaft Di	ameter:
0.0895 in	nches single shaft and 0.0900 inches single shaft
Shaft Le	ength:
0.3750 in	nches single shaft
Fragility	Factor:
Moderat	ely rugged
Body Si	ze:
8	
Stator Ir	nput Voltage Rating In Volts:
11.8	
Stator In	nput Current Rating:
30.0 mill	iamperes
Stator In	nput Electrical Power Rating:
73.0 mill	iwatts
Frequen	ncy In Hertz:
400.0	

Zro Resistance In Ohms:

470.00

Zso Resistance In Ohms:

81.00

Zrs Resistance In Ohms:

590.00

Rotor Dc Resistance In Ohms:

365.00

Stator Dc Resistance In Ohms:

64.00

NSN 5990-00-688-4759 Control Transformer Synchro - Page 2 of 2



Phase Shift Angle In Deg:
8.500 input to output
Maximum Total Null Voltage Output In Millivolts Per Volt:
30.00
Electrical Error Angular Range In Minutes:
-7.0/+7.0
Actuator Friction Torque At Minus 55 Deg Celsius:
6.0 centimeter-grams
Actuator Friction Torque At Plus 25 Deg Celsius:
3.0 centimeter-grams
Pilot Length:
0.0430 inches
Mounting Surface To Terminal End Distance:
1.2410 inches
Terminal Location:
Rear
Plus J Zro Reactance In Ohms:
1770.00
Shaft Slot Depth:
0.0250 inches single shaft
Plus J Zso Reactance In Ohms:
330.00
Shaft Slot Width:
0.0200 inches single shaft
Plus J Zrs Reactance In Ohms:
190.00
Shaft Type:
Round, slotted single shaft
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A07800