NSN 5990-00-689-5736

Receiver Synchro - Page 1 of 2

Body Material:

Aluminum

Body Style:



View Online at https://aerobasegroup.com/nsn/5990-00-689-5736

Standard round c
Shoulder Diameter:
Between 0.8118 inches and 0.8123 inches
Pilot Diameter:
Between 0.4995 inches and 0.5000 inches
Overall Length:
1.5340 inches
Flange Diameter:
Between 0.9360 inches and 0.9370 inches
Flange Thickness:
0.0630 inches
Undercut Diameter:
Between 0.8370 inches and 0.8400 inches
Undercut Width:
0.0620 inches
Shaft Diameter:
0.0880 inches single shaft and 0.0900 inches single shaft
Shaft Length:
0.2930 inches single shaft
Fragility Factor:
Moderately rugged
Body Size:
10
Rotor Input Voltage Rating In Volts:
115.0
Frequency In Hertz:
400.0
Rotor Input Current Rating:
37.0 milliamperes
Rotor Input Electrical Power Rating:
1.0 watts
Rotor Dc Resistance In Ohms:
500.00
Stator Dc Resistance In Ohms:
7.30
Phase Shift Angle In Deg:
8.500 input to output
Electrical Error Angular Range In Minutes:
-15.0/+15.0

NSN 5990-00-689-5736

Receiver Synchro - Page 2 of 2



Actuator Friction Torque At Minus 55 Deg Celsius:
5400.0 millimeter-milligrams
Actuator Friction Torque At Plus 25 Deg Celsius:
2700.0 millimeter-milligrams
Pilot Length:
0.0380 inches
Shoulder Length:
0.0620 inches
Mounting Surface To Terminal End Distance:
1.2410 inches
Terminal Location:
Rear
Shaft Type:
Round single shaft
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A07800