

View Online at <https://aerobasegroup.com/nsn/5990-00-702-7640>

**Body Material:**

Steel, corrosion resisting

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.9995 inches and 1.0000 inches

**Pilot Diameter:**

Between 0.6245 inches and 0.6250 inches

**Overall Length:**

2.1400 inches

**Flange Diameter:**

Between 1.0590 inches and 1.0620 inches

**Flange Thickness:**

0.0930 inches

**Undercut Diameter:**

0.9750 inches

**Undercut Width:**

0.0500 inches

**Shaft Diameter:**

0.1195 inches single shaft and 0.1200 inches single shaft

**Shaft Length:**

0.5000 inches single shaft

**Body Size:**

11

**Stator Input Voltage Rating In Volts:**

11.8

**Stator Input Current Rating:**

151.0 milliamperes

**Stator Input Electrical Power Rating:**

350.0 milliwatts

**Frequency In Hertz:**

400.0

**Zro Resistance In Ohms:**

21.00

**Zso Resistance In Ohms:**

15.00

**Zrs Resistance In Ohms:**

16.60

**Rotor Dc Resistance In Ohms:**

14.30

**Stator Dc Resistance In Ohms:**

8.50

**Phase Shift Angle In Deg:**

5.000 input to output

**Maximum Fundamental Null Voltage In Millivolts Per Volt:**

22.000 output

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

30.00

**Actuator Friction Torque At Minus 55 Deg Celsius:**

9.00 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

3.00 centimeter-grams

**Pilot Length:**

0.0620 inches

**Shoulder Length:**

0.0620 inches

**Mounting Surface To Terminal End Distance:**

1.6400 inches

**Terminal Location:**

Rear

**Plus J Zro Reactance In Ohms:**

84.00

**Shaft Slot Depth:**

0.0200 inches single shaft and 0.0320 inches single shaft

**Plus J Zso Reactance In Ohms:**

72.00

**Shaft Slot Width:**

0.0220 inches single shaft and 0.0320 inches single shaft

**Plus J Zrs Reactance In Ohms:**

8.30

**Shaft Type:**

Round, slotted single shaft

**Transformation Ratio:**

1.154 rotor to stator

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A07800