

View Online at <https://aerobasegroup.com/nsn/5990-00-724-3087>

**Body Material:**

Steel, stainless

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.9995 inches and 1.0000 inches

**Pilot Diameter:**

Between 0.6245 inches and 0.6250 inches

**Overall Length:**

Between 2.4890 inches and 2.5130 inches

**Flange Diameter:**

Between 1.0570 inches and 1.0650 inches

**Flange Thickness:**

0.0930 inches

**Undercut Diameter:**

0.9750 inches

**Undercut Width:**

0.0500 inches

**Shaft Diameter:**

0.1200 inches single shaft

**Shaft Length:**

0.5620 inches single shaft

**Body Size:**

11

**Stator Input Voltage Rating In Volts:**

11.8

**Stator Input Current Rating:**

21.0 milliamperes

**Stator Input Electrical Power Rating:**

30.0 milliwatts

**Frequency In Hertz:**

400.0

**Zro Impedance Magnitude In Ohms:**

3340.00

**Zro Impedance Angle In Deg:**

79.20

**Zso Impedance Magnitude In Ohms:**

577.00

**Zso Impedance Angle In Deg:**

80.70

**Zrs Impedance Magnitude In Ohms:**

659.00

**Zrs Impedance Angle In Deg:**

30.10

**Phase Shift Angle In Deg:**

4.200 input to output

**Electrical Error Angular Range In Minutes:**

-5.0/+5.0

**Actuator Friction Torque At Minus 55 Deg Celsius:**

16.0 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

4.0 centimeter-grams

**Pilot Length:**

0.0620 inches

**Shoulder Length:**

0.0620 inches

**Mounting Surface To Terminal End Distance:**

1.7960 inches

**Terminal Location:**

Rear

**Shaft Slot Depth:**

0.0300 inches single shaft

**Shaft Slot Width:**

0.0250 inches single shaft

**Shaft Type:**

Round, slotted single shaft

**Transformation Ratio:**

2.203 rotor to stator

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A07800