NSN 5990-00-726-3516



Control Transformer Synchro - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5990-00-726-3516

Body Material:
Steel, corrosion resisting
Body Style:
Standard round c
Shoulder Diameter:
Between 0.8118 inches and 0.8123 inches
Pilot Diameter:
Between 0.4995 inches and 0.5000 inches
Overall Length:

1.6160 inches

Flange Diameter:

Between 0.9360 inches and 0.9370 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.8350 inches and 0.8400 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.4130 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

10

Stator Input Voltage Rating In Volts:

10.2

Stator Input Current Rating:

70.0 milliamperes

Stator Input Electrical Power Rating:

200.0 milliwatts

Frequency In Hertz:

400.0

Zso Resistance In Ohms:

43.00

Rotor Dc Resistance In Ohms:

135.00

Stator Dc Resistance In Ohms:

36.00

Phase Shift Angle In Deg:

10.000 input to output

NSN 5990-00-726-3516 Control Transformer Synchro - Page 2 of 2



Actuator Friction Torque At Minus 55 Deg Celsius:
15.0 centimeter-grams
Actuator Friction Torque At Plus 25 Deg Celsius:
4.0 centimeter-grams
Alignment Hole Quantity:
3
Pilot Length:
0.0380 inches
Shoulder Length:
0.0630 inches
Mounting Surface To Terminal End Distance:
1.2410 inches
Terminal Location:
Rear
Shaft Slot Depth:
0.0470 inches single shaft
Plus J Zso Reactance In Ohms:
141.00
Shaft Slot Width:
0.0470 inches single shaft
Shaft Type:
Round, slotted single shaft
Alignment Hole Depth:
0.0620 inches
Alignment Hole Bolt Circle Diameter:
0.6780 inches
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A07800