NSN 5990-00-730-4366

Body Material:

Steel, corrosion resisting

Control Transformer Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-730-4366

Body Style:	
Standard round a	
Pilot Diameter:	
Between 0.4995 inches and 0.5000 inches	
Overall Length:	
1.7840 inches	
Flange Diameter:	
Between 0.7490 inches and 0.7500 inches	
Flange Thickness:	
0.0620 inches	
Undercut Diameter:	
Between 0.6880 inches and 0.6910 inches	
Undercut Width:	
0.0620 inches	
Shaft Diameter:	
0.0895 inches single shaft and 0.0900 inches single shaft	
Shaft Length:	
0.5430 inches single shaft	
Body Size:	
8	
Otatan Innest Valtana Bathan In Valtas	
Stator Input Voltage Rating In Volts:	
11.8	
11.8	
11.8 Stator Input Current Rating:	
11.8 Stator Input Current Rating: 87.0 milliamperes	
11.8 Stator Input Current Rating: 87.0 milliamperes Stator Input Electrical Power Rating:	
11.8 Stator Input Current Rating: 87.0 milliamperes Stator Input Electrical Power Rating: 210.0 milliwatts	
11.8 Stator Input Current Rating: 87.0 milliamperes Stator Input Electrical Power Rating: 210.0 milliwatts Frequency In Hertz:	
11.8 Stator Input Current Rating: 87.0 milliamperes Stator Input Electrical Power Rating: 210.0 milliwatts Frequency In Hertz: 400.0	
11.8 Stator Input Current Rating: 87.0 milliamperes Stator Input Electrical Power Rating: 210.0 milliwatts Frequency In Hertz: 400.0 Actuator Friction Torque At Minus 55 Deg Celsius:	
11.8 Stator Input Current Rating: 87.0 milliamperes Stator Input Electrical Power Rating: 210.0 milliwatts Frequency In Hertz: 400.0 Actuator Friction Torque At Minus 55 Deg Celsius: 16.0 centimeter-grams	
Stator Input Current Rating: 87.0 milliamperes Stator Input Electrical Power Rating: 210.0 milliwatts Frequency In Hertz: 400.0 Actuator Friction Torque At Minus 55 Deg Celsius: 16.0 centimeter-grams Actuator Friction Torque At Plus 25 Deg Celsius:	
Stator Input Current Rating: 87.0 milliamperes Stator Input Electrical Power Rating: 210.0 milliwatts Frequency In Hertz: 400.0 Actuator Friction Torque At Minus 55 Deg Celsius: 16.0 centimeter-grams Actuator Friction Torque At Plus 25 Deg Celsius: 4.0 centimeter-grams Pilot Length: 0.0430 inches	
Stator Input Current Rating: 87.0 milliamperes Stator Input Electrical Power Rating: 210.0 milliwatts Frequency In Hertz: 400.0 Actuator Friction Torque At Minus 55 Deg Celsius: 16.0 centimeter-grams Actuator Friction Torque At Plus 25 Deg Celsius: 4.0 centimeter-grams Pilot Length:	
Stator Input Current Rating: 87.0 milliamperes Stator Input Electrical Power Rating: 210.0 milliwatts Frequency In Hertz: 400.0 Actuator Friction Torque At Minus 55 Deg Celsius: 16.0 centimeter-grams Actuator Friction Torque At Plus 25 Deg Celsius: 4.0 centimeter-grams Pilot Length: 0.0430 inches	
Stator Input Current Rating: 87.0 milliamperes Stator Input Electrical Power Rating: 210.0 milliwatts Frequency In Hertz: 400.0 Actuator Friction Torque At Minus 55 Deg Celsius: 16.0 centimeter-grams Actuator Friction Torque At Plus 25 Deg Celsius: 4.0 centimeter-grams Pilot Length: 0.0430 inches Mounting Surface To Terminal End Distance:	
Stator Input Current Rating: 87.0 milliamperes Stator Input Electrical Power Rating: 210.0 milliwatts Frequency In Hertz: 400.0 Actuator Friction Torque At Minus 55 Deg Celsius: 16.0 centimeter-grams Actuator Friction Torque At Plus 25 Deg Celsius: 4.0 centimeter-grams Pilot Length: 0.0430 inches Mounting Surface To Terminal End Distance: 1.2410 inches	
Stator Input Current Rating: 87.0 milliamperes Stator Input Electrical Power Rating: 210.0 milliwatts Frequency In Hertz: 400.0 Actuator Friction Torque At Minus 55 Deg Celsius: 16.0 centimeter-grams Actuator Friction Torque At Plus 25 Deg Celsius: 4.0 centimeter-grams Pilot Length: 0.0430 inches Mounting Surface To Terminal End Distance: 1.2410 inches Terminal Location:	

NSN 5990-00-730-4366

Control Transformer Synchro - Page 2 of 2



Shaft Slot Width	aft Slot Width	1:
------------------	----------------	----

0.0320 inches single shaft

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800