## NSN 5990-00-732-9261

Control Transformer Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-732-9261

View Online at https://aerobasegroup.com/nsn/5990-00-732
Body Material:
Steel, corrosion resisting
Body Style:
Standard round c
Shoulder Diameter:
Between 1.3115 inches and 1.3120 inches
Pilot Diameter:
Between 0.4995 inches and 0.5000 inches
Overall Length:
2.1000 inches
Flange Diameter:
Between 1.4360 inches and 1.4370 inches
Flange Thickness:
0.0930 inches
Undercut Diameter:
1.3120 inches
Undercut Width:
0.0780 inches
Shaft Diameter:
$0.1195 \ \text{inches} \ \ \text{single} \ \ \text{shaft} \ \ \ \text{and} \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \$
Shaft Length:
0.5400 inches single shaft
Body Size:
15
Stator Input Voltage Rating In Volts:
26.0
Stator Input Current Rating:
7.0 milliamperes
Stator Input Electrical Power Rating:
14.0 milliwatts
Frequency In Hertz:
400.0
Actuator Friction Torque At Minus 55 Deg Celsius:
16.0 centimeter-grams
Actuator Friction Torque At Plus 25 Deg Celsius:
4.0 centimeter-grams
Pilot Length:
0.0400 inches
Shoulder Length:
0.1320 inches
Mounting Surface To Terminal End Distance:

**Mounting Surface To Terminal End Distance:** 1.5600 inches

## NSN 5990-00-732-9261

Control Transformer Synchro - Page 2 of 2



Terminal Location:
Rear
Shaft Slot Depth:
0.0220 inches single shaft and 0.0320 inches single shaft
Shaft Slot Width:
0.0220 inches single shaft and 0.0320 inches single shaft
Shaft Type:
Round, slotted single shaft
Transformation Ratio:
2.215 rotor to stator
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
Δ07800