

View Online at <https://aerobasegroup.com/nsn/5990-00-753-8870>

Body Material:

Steel, stainless

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

Between 1.5990 inches and 1.6150 inches

Flange Diameter:

Between 0.7445 inches and 0.7450 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.6910 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.1195 inches single shaft and 0.1200 inches single shaft

Shaft Length:

0.3590 inches single shaft and 0.3750 inches single shaft

Body Size:

8

Stator Input Voltage Rating In Volts:

26.0

Stator Input Current Rating:

18.0 milliamperes

Stator Input Electrical Power Rating:

70.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

550.00

Zso Resistance In Ohms:

467.00

Zrs Resistance In Ohms:

795.00

Rotor Dc Resistance In Ohms:

560.00

Stator Dc Resistance In Ohms:

350.00

Phase Shift Angle In Deg:

8.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-4.0/+4.0

Actuator Friction Torque At Minus 55 Deg Celsius:

15.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Pilot Length:

Between 0.0400 inches and 0.0430 inches

Mounting Surface To Terminal End Distance:

1.2400 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

2000.00

Shaft Slot Depth:

0.0310 inches single shaft

Plus J Zso Reactance In Ohms:

600.00

Shaft Slot Width:

0.0250 inches single shaft

Plus J Zrs Reactance In Ohms:

310.00

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

1.000 rotor to stator

Terminal Type And Quantity:

7 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800