

View Online at <https://aerobasegroup.com/nsn/5990-00-764-7487>

Body Material:

Steel, stainless

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6200 inches

Flange Diameter:

Between 0.7450 inches and 0.7530 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

0.6870 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.3750 inches single shaft

Maximum Temperature Rise:

9.0 degrees celsius

Body Size:

8

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

105.0 milliamperes

Rotor Input Electrical Power Rating:

750.0 milliwatts

Zro Impedance Magnitude In Ohms:

270.00

Zro Impedance Angle In Deg:

75.00

Zso Impedance Magnitude In Ohms:

50.00

Zso Impedance Angle In Deg:

70.00

Rotor Dc Resistance In Ohms:

45.00

Stator Dc Resistance In Ohms:

15.00

Phase Shift Angle In Deg:

15.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

22.00 output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-5.0/+5.0

Actuator Friction Torque At Minus 55 Deg Celsius:

12.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.0 centimeter-grams

Pilot Length:

0.0400 inches

Mounting Surface To Terminal End Distance:

1.2450 inches

Terminal Location:

Rear

Shaft Slot Depth:

0.0300 inches single shaft

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800