

View Online at <https://aerobasegroup.com/nsn/5990-00-779-5210>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6740 inches

Flange Diameter:

Between 0.7470 inches and 0.7510 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

Between 0.6900 inches and 0.6930 inches

Undercut Width:

0.0620 inches

Shaft Diameter:

0.0895 inches single shaft and 0.0900 inches single shaft

Shaft Length:

0.4160 inches single shaft

Fragility Factor:

Moderately rugged

Body Size:

8

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

110.0 milliamperes

Rotor Input Electrical Power Rating:

690.0 milliwatts

Zro Resistance In Ohms:

58.00

Zso Resistance In Ohms:

125.00

Rotor Dc Resistance In Ohms:

38.00

Stator Dc Resistance In Ohms:

11.80

Phase Shift Angle In Deg:

10.000 input to output

Maximum Total Null Voltage Output In Millivolts Per Volt:

30.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Plus 25 Deg Celsius:

0.03 centimeter-grams

Torque Gradient Per Angular Deg:

1.500 inch-ounces

Pilot Length:

0.0410 inches

Mounting Surface To Terminal End Distance:

1.2410 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

234.00

Shaft Slot Depth:

0.0300 inches single shaft

Plus J Zso Reactance In Ohms:

40.00

Shaft Slot Width:

0.0250 inches single shaft

Shaft Type:

Round, slotted single shaft

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A07800