

View Online at <https://aerobasegroup.com/nsn/5990-00-782-0023>

Body Material:

Any acceptable

Body Style:

Standard round c

Shoulder Diameter:

Between 0.9995 inches and 1.0000 inches

Pilot Diameter:

Between 0.6245 inches and 0.6250 inches

Overall Length:

2.1620 inches

Flange Diameter:

Between 1.0610 inches and 1.0620 inches

Flange Thickness:

0.0930 inches

Undercut Diameter:

0.9750 inches

Undercut Width:

0.0500 inches

Shaft Diameter:

0.1195 inches front shaft and 0.1200 inches front shaft

Shaft Length:

0.5470 inches front shaft and 0.5770 inches front shaft

Body Size:

11

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

240.0 milliamperes

Rotor Input Electrical Power Rating:

920.0 milliwatts

Zro Resistance In Ohms:

16.00

Zso Resistance In Ohms:

3.70

Zrs Resistance In Ohms:

22.00

Rotor Dc Resistance In Ohms:

8.50

Stator Dc Resistance In Ohms:

3.00

Phase Shift Angle In Deg:

5.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

30.00 output

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

16.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

4.0 centimeter-grams

Pilot Length:

Between 0.0590 inches and 0.0650 inches

Shoulder Length:

Between 0.0590 inches and 0.0650 inches

Mounting Surface To Terminal End Distance:

1.6000 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

107.00

Shaft Slot Depth:

0.0220 inches front shaft and 0.0320 inches front shaft

Plus J Zso Reactance In Ohms:

18.10

Shaft Slot Width:

0.0220 inches front shaft and 0.0320 inches front shaft

Plus J Zrs Reactance In Ohms:

8.90

Shaft Type:

Round, slotted front shaft

Transformation Ratio:

0.454 rotor to stator

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A07800