

View Online at <https://aerobasegroup.com/nsn/5990-00-782-0025>

Body Material:

Steel, corrosion resisting

Body Style:

Standard round c

Shoulder Diameter:

0.9750 inches

Pilot Diameter:

0.6250 inches

Overall Length:

1.9850 inches

Flange Diameter:

1.9850 inches

Flange Thickness:

0.0620 inches

Undercut Diameter:

1.0000 inches

Undercut Width:

0.0810 inches

Shaft Diameter:

0.1200 inches single shaft

Shaft Length:

0.5630 inches single shaft

Body Size:

11

Stator Input Voltage Rating In Volts:

26.0

Stator Input Current Rating:

20.0 milliamperes

Stator Input Electrical Power Rating:

45.0 milliwatts

Frequency In Hertz:

400.0

Zro Resistance In Ohms:

20.00

Zso Resistance In Ohms:

4.30

Zrs Resistance In Ohms:

25.00

Rotor Dc Resistance In Ohms:

10.50

Stator Dc Resistance In Ohms:

3.60

Phase Shift Angle In Deg:

4.000 input to output

Maximum Fundamental Null Voltage In Millivolts Per Volt:

30.00 input

Maximum Total Null Voltage Output In Millivolts Per Volt:

70.00

Electrical Error Angular Range In Minutes:

-7.0/+7.0

Actuator Friction Torque At Minus 55 Deg Celsius:

15.0 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

5.0 centimeter-grams

Pilot Length:

0.0620 inches

Shoulder Length:

0.0620 inches

Mounting Surface To Terminal End Distance:

1.6000 inches

Terminal Location:

Rear

Plus J Zro Reactance In Ohms:

150.00

Shaft Slot Depth:

0.0320 inches single shaft

Plus J Zso Reactance In Ohms:

24.60

Shaft Slot Width:

0.0320 inches single shaft

Plus J Zrs Reactance In Ohms:

12.20

Shaft Type:

Round, slotted single shaft

Transformation Ratio:

2.203 rotor to stator

Terminal Type And Quantity:

5 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07800