

View Online at <https://aerobasegroup.com/nsn/5990-00-784-0910>

Body Style:

Standard round a

Pilot Diameter:

Between 0.4995 inches and 0.5000 inches

Overall Length:

1.6680 inches

Flange Diameter:

Between 0.7450 inches and 0.7530 inches

Flange Thickness:

Between 0.0590 inches and 0.0650 inches

Undercut Width:

Between 0.0590 inches and 0.0650 inches

Shaft Diameter:

0.1195 inches single shaft

Shaft Length:

0.3780 inches single shaft and 0.4020 inches single shaft

Maximum Temperature Rise:

9.0 degrees celsius

Body Size:

13

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

114.0 milliamperes

Rotor Input Electrical Power Rating:

650.0 milliwatts

Zrs Resistance In Ohms:

120.00

Zro Impedance Magnitude In Ohms:

52.00

Zro Impedance Angle In Deg:

71.00

Zso Impedance Magnitude In Ohms:

269.00

Zso Impedance Angle In Deg:

75.00

Rotor Dc Resistance In Ohms:

Between 50.00 and 68.00

Stator Dc Resistance In Ohms:

Between 15.30 and 20.70

Phase Shift Angle In Deg:

13.000 input to output

Actuator Friction Torque At Minus 55 Deg Celsius:

12.00 centimeter-grams

Actuator Friction Torque At Plus 25 Deg Celsius:

3.00 centimeter-grams

Pilot Length:

Between 0.0370 inches and 0.0430 inches

Mounting Surface To Terminal End Distance:

1.2400 inches

Terminal Location:

Rear

Plus J Zrs Reactance In Ohms:

38.00

Shaft Type:

Round single shaft

Transformation Ratio:

Between 0.436 rotor to stator and 0.472 rotor to stator

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A07800