NSN 5990-00-784-0910

Transmitter Synchro - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5990-00-784-0910

Body Style:
Standard round a

Pilot Diameter:
Between 0.4995 inches and 0.5000 inches

Overall Length:
1.6680 inches

Flange Diameter:

Flange Thickness:

Between 0.0590 inches and 0.0650 inches

Between 0.7450 inches and 0.7530 inches

Undercut Width:

Between 0.0590 inches and 0.0650 inches

Shaft Diameter:

0.1195 inches single shaft

Shaft Length:

0.3780 inches single shaft and 0.4020 inches single shaft

Maximum Tempurature Rise:

9.0 degrees celsius

...

Body Size:

13

Rotor Input Voltage Rating In Volts:

26.0

Frequency In Hertz:

400.0

Rotor Input Current Rating:

114.0 milliamperes

Rotor Input Electrical Power Rating:

650.0 milliwatts

Zrs Resistance In Ohms:

120.00

Zro Impedance Magnitude In Ohms:

52.00

Zro Impedance Angle In Deg:

71.00

Zso Impedance Magnitude In Ohms:

269.00

Zso Impedance Angle In Deg:

75.00

Rotor Dc Resistance In Ohms:

Between 50.00 and 68.00

Stator Dc Resistance In Ohms:

Between 15.30 and 20.70

NSN 5990-00-784-0910 Transmitter Synchro - Page 2 of 2



Phase Shift Angle In Deg:
13.000 input to output
Actuator Friction Torque At Minus 55 Deg Celsius:
12.00 centimeter-grams
Actuator Friction Torque At Plus 25 Deg Celsius:
3.00 centimeter-grams
Pilot Length:
Between 0.0370 inches and 0.0430 inches
Mounting Surface To Terminal End Distance:
1.2400 inches
Terminal Location:
Rear
Plus J Zrs Reactance In Ohms:
38.00
Shaft Type:
Round single shaft
Transformation Ratio:
Between 0.436 rotor to stator and 0.472 rotor to stator
Terminal Type And Quantity:
5 wire lead
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Fiig:
407800