

View Online at <https://aerobasegroup.com/nsn/5990-00-784-5557>

**Body Material:**

Steel, stainless

**Body Style:**

Standard round c

**Shoulder Diameter:**

Between 0.8118 inches and 0.8123 inches

**Pilot Diameter:**

Between 0.4995 inches and 0.5000 inches

**Overall Length:**

1.5310 inches

**Flange Diameter:**

Between 0.9360 inches and 0.9370 inches

**Flange Thickness:**

0.0630 inches

**Undercut Diameter:**

Between 0.8370 inches and 0.8400 inches

**Undercut Width:**

0.0620 inches

**Shaft Diameter:**

0.0880 inches single shaft and 0.0900 inches single shaft

**Shaft Length:**

0.2500 inches single shaft

**Body Size:**

10

**Stator Input Voltage Rating In Volts:**

2.0

**Rotor Input Voltage Rating In Volts:**

2.0

**Frequency In Hertz:**

10000.0

**Phase Shift Angle In Deg:**

1.000 input to output

**Maximum Total Null Voltage Output In Millivolts Per Volt:**

40.00

**Actuator Friction Torque At Minus 55 Deg Celsius:**

9.0 centimeter-grams

**Actuator Friction Torque At Plus 25 Deg Celsius:**

3.0 centimeter-grams

**Alignment Hole Quantity:**

3

**Pilot Length:**

0.0380 inches

**Shoulder Length:**

0.0620 inches

**Mounting Surface To Terminal End Distance:**

1.2810 inches

**Terminal Location:**

Rear

**Shaft Slot Depth:**

0.0460 inches single shaft

**Shaft Slot Width:**

0.0460 inches single shaft

**Shaft Type:**

Round, slotted single shaft

**Alignment Hole Depth:**

0.0500 inches

**Transformation Ratio:**

1.800 rotor to stator

**Alignment Hole Bolt Circle Diameter:**

0.6780 inches

**Terminal Type And Quantity:**

8 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A07800